

Series SVBK



Inline centrifugal fans in plastic casing
with the air flow up to **1700 m³/h**

Applications

SVBK fans are applied for supply and exhaust ventilation systems of commercial, office and other premises. Compatible with Ø 100, 125, 150, 200, 250 and 315 mm round air ducts. Models marked SVBK...Q are supplied with quiet motors for low-noise applications. Due to the corrosion-resistant durable plastic casing, these models are the perfect solution for the installation in exhaust ventilation systems in humid premises such as bathrooms, kitchens etc.



Design

The casing is made of high-quality durable plastic. The fans are equipped with waterproof terminal boxes. Models marked SVBK..R are supplied with the power cord and a plug.



Motor

The centrifugal impeller with backward curved blades is powered by a single-phase external rotor motor. The motor is equipped with self-resetting overheating protection. Some standard sizes are available with a high-powered motor, see the SVBK modifications. The motor is equipped with ball bearings for a long service life.

life designed for at least 40 000 operating hours. For precise features, safe operation and low noise, each impeller is dynamically balanced while assembly. Motor protection rating is IP 44.

The double-speed models (Duo) are equipped with asynchronous electric external rotor motors and centrifugal impellers with forward curved blades. The impellers are dynamically balanced. Double-speed control.


Speed control

Smooth or step speed control with a thyristor or autotransformer speed controller. Several fans may be connected to one speed controller provided that the total power and operating current do not exceed the rated speed controller parameters.

Two-speed models are controlled with the external speed switch P2-10 (available separately).

Mounting

The fan is mounted to the wall or ceiling with mounting brackets included into delivery set or with PVK holders, specially ordered accessory. The fan can be mounted at any angle. Electric connection and installation shall be



Designation key

Series		Duct diameter	Options
SVBK	S: high-powered motor	100; 125; 150*; 200; 250; 315	Q: low-powered motor. Duo: double-speed motor. U: speed controller with an electronic thermostat and a temperature sensor integrated into the air duct. Equipped with a power cord and an IEC C14 electric plug. Temperature-based operation logic. Un: speed controller with an electronic thermostat and external temperature sensor fixed on 4 m cable. Equipped with a power cord and an IEC C14 electric plug. Temperature-based operation logic. U1: speed controller with an electronic thermostat and a temperature sensor integrated into the air duct. Equipped with a power cord and an IEC C14 electric plug. Timer-based operation logic. U1n: speed controller with an electronic thermostat and external temperature sensor fixed on 4 m cable. Equipped with a power cord and an IEC C14 electric plug. Timer-based operation logic. P: built-in smooth speed controller and power cord with an IEC C14 electric plug. V: built-in speed switch (for models with double-speed motors). R: power cord with an IEC C14 electric plug.

*SVBK 150 model is compatible with the air ducts both Ø 150 and 160 mm

Accessories



Silencer



Filters



Heaters



Backdraft damper



Air shutter



Speed controllers



Speed switch



performed in compliance with the manual and the wiring diagram on the terminal box.

■ Fan with electronic temperature and control module (U option)

The ideal solution for ventilation of the premises requiring permanent temperature control, i.e. greenhouses. The fan with the electronic temperature and speed control module provides automatic control of the motor speed (air flow) depending on air temperature in the air duct or in the room.

The front panel of the electronic module has the following control knobs:

- speed control knob for setting the motor speed
- thermostat control knob for setting the temperature set point
- thermostat indicator light

The fan is available in two modifications:

- with the temperature sensor integrated inside the fan air duct (U/U1 option)

– with the external temperature sensor fixed on the cable, 4 m long (Un / U1n)

■ Control logic of the fan with the electronic temperature and speed control module

Set the desired air temperature (thermostat set point) by turning the thermostat control knob. Set the required minimum impeller speed (air flow) by turning the speed control knob. The motor switches to maximum speed (maximum air flow) as the temperature reaches and exceeds the set temperature set point. The motor switches to the pre-set lower speed as the temperature drops down below the temperature set point. To avoid frequent motor speed switches when the air temperature in the duct is equal to the set temperature point, the speed switch delay is activated. There are two switch delay patterns for various cases:

1. The temperature sensor-based switch delay (U option): the motor switches to higher speed as the

air temperature exceeds 2 °C above the set thermostat set point. The motor reverts to the preset lower speed as the air temperature drops below the thermostat set point. This pattern is used to keep air temperature to within 2 °C. In this case the motor speed switches are rare.

2. The timer-based switch delay (U1 option): as the air temperature exceeds the set thermostat set point, the motor switches to higher speed and the switch delay timer is activated for 5 min. The motor reverts to lower speed as the air temperature drops down below the thermostat set point and only after 5 minutes timer countdown.

This pattern is used for exact air temperature control. The speed switches for the fan with U1 option are more frequent as compared to the operating logic of the fan with U option, however the minimum operating cycle at one speed is 5 minutes.

■ Example for temperature sensor delay pattern:

Initial conditions:

- rated speed is set as 60 % of the maximum speed
- operating threshold is set as 25 °C
- air temperature in the duct is 20 °C

motor operates with the rated speed =60 %

- air temperature in the duct rises

motor operates with the rated speed =60 %

- air temperature in the duct reaches 27 °C

motor switches to the speed =100 %

- air temperature in the duct goes down

motor operates with the speed =100 %

- temperature in the duct reaches 25 °C again

motor switches to the preset rated speed =60 %

■ Example for timer delay pattern:

Initial conditions:

- rated speed is set as 60 % of maximum speed
- operating threshold is set as 25 °C
- air temperature in the duct is 20 °C

motor operates with the rated speed =60 %

- the temperature in the duct rises, reaches 25 °C and keeps rising

- fan switches to the maximum speed =100 % and the delay timer switches on again for 5 minutes

- the temperature in the duct goes down

the motor operates with the maximum speed =100 %

- the temperature in the duct reaches 25 °C and keeps rising

- after the timer stops, the motor switches to the preset rated speed (=60 %). After the speed switch, the timer switches on again for 5 minutes.

- the temperature in the duct rises, reaches 25 °C and keeps rising

- after the timer stops, the motor switches to the maximum speed (=100 %). After the speed switch, the delay timer switches on again for 5 minutes





Thus, in timer delay pattern the delay timer activates every time when the fan speed changes.



FANS FOR ROUND DUCTS

Technical data

	SVBK 100 Q		SVBK 100		SVBK 125 Q		SVBK 125		SVBK 150	
Voltage [V]	1~230		1~230		1~230		1~230		1~230	
Frequency [Hz]	50	60	50	60	50	60	50	60	50	60
Power [W]	62	63	80	81	61	64	79	81	80	84
Current [A]	0.38	0.38	0.34	0.34	0.38	0.4	0.34	0.35	0.35	0.37
Maximum air flow [m³/h]	205	210	250	290	260	270	355	370	460	505
RPM [min⁻¹]	2650	2710	2820	2890	2610	2680	2800	2830	2725	2840
Noise level at 3 m [dBA]	36	36	40	41	36	37	40	41	42	43
Transported air temperature [°C]	-25 +55	-25 +50	-25 +55	-25 +50	-25 +55	-25 +50	-25 +55	-25 +50	-25 +55	-25 +50
SEC class	C	-	C	-	C	-	B	-	B	-
Protection rating	IPX4	IPX4	IPX4	IPX4	IPX4	IPX4	IPX4	IPX4	IPX4	IPX4



Technical data

	SVBK 200		SVBK 200		SVBK 250 Q		SVBK 250		SVBK 315	SVBK 315
Voltage [V]	1~230		1~230		1~230		1~220-240		1~230	1~230
Frequency [Hz]	50	60	50	60	50	60	50	60	50	50
Power [W]	107	132	173	216	108	135	173	207	200	310
Current [A]	0.47	0.58	0.76	0.94	0.47	0.9	0.76	0.9	0.88	1.36
Maximum air flow [m ³ /h]	780	890	930	1020	865	930	1080	1090	1340	1700
RPM [min ⁻¹]	2660	2765	2125	2155	2560	2570	2090	2120	2655	2590
Noise level at 3 m [dBA]	46	46	48	49	47	48	49	50	48	57
Transported air temperature [°C]	-25 +55	-25 +50	-25 +55	-25 +45	-25 +55	-25 +50	-25 +55	-25 +50	-25 +55	-25 +45
SEC class	B	-	B	-	B	-	B	-	-	-
Protection rating	IPX4	IPX4	IPX4	IPX4	IPX4	IPX4	IPX4	IPX4	IPX4	IPX4

